

Calibration Tables

Model	A & D												Note
	Readability		Calibration			Repeatability		Corner Load		Linearity			
	Capacity	Res	Weight	Tol	Class	Weight	Tol	Weight	Tol	Weigh	Preload	Tol	
EK120A	120	.01	100	1	4/P	100	1	na	0	50	50	1	
EK12KA	12K	1	10K	1	4/P	10K	1	na	0	5K	5K	1	
EK2000	2K	.1	2K	1	4/P	2K	1	na	0	1K	1K	1	
EK200G	200	.01	200	1	4/P	200	1	na	0	100	100	1	
EK6000	6K	1	6K	1	4/P	5K	1	na	0	3K	3K	1	
EK600G	600	.1	600	1	4/P	500	1	na	0	300	300	1	
EP12	12K	.1	10K	1	2	10K	1	5K	2	5K	5K	2	
EP20	20K	.1	20K	1	2	20K	1	10K	2	10K	10K	2	
EP22	20K/2K	1/1	20K	1		30K	5	10K	2	10K	10K	1	
EP30	30K	.1	30K	2	1/S	30K	5	10K	2	10K	20K	2	
EP40	40K	.5	40K	1	3	40K	5	20K	2	20K	20K	1	
EP41	40K	1	40K	1	4/P	40K	5	20K	2	20K	20K	1	
EP60	60K	1	60K	1	3	50K	5	30K	2	30K	30K	1	
ER120A	120	.0001	100	1	*	100	1	100	2	50	50	2	
ER180A	180	.0001	100	1	*	100	1	100	2	50	100	2	
ER182	180/32	.0001/.00001	100	1		100/20	1/2	100	2	50	100	2	
ER60A	60	.0001	50	1	*	50	1	50	2	20	40	2	
ET120A	120	.01	100	1	4/P	100	1	na	0	50	50	1	
FP12K	12K	.1	10K	1	2	10K	1	6K	2	5K	5K	1	
FP6000	6100	.01	5K	2	*	5K	1	3K	2	3K	3K	2	
FP6200	6100/1000	.1/.01	5K	2		5K	1	3K	2	3K	3K	2	
FR200	210	.0001	200	1	*	200	2	100	2	100	100	2	

11/21/01

Page 1 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

A & D

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
FR300	310	.0001	300	1	*	300	2	150	2	100	200	3	
FX1200	1200	.01	1K	1	2	1K	1	500	3	500	500	3	
FX200	200	.001	200	1	2	200	1	100	2	100	100	2	
FX2000	2K	.01	2K	1	2	2K	1	1K	2	1K	1K	2	
FX300	310	.001	200	1	1/S	300	1	200	2	100	200	2	
FX3000	3K	.01	2K	1	1/S	3K	1	2K	2	1K	2K	2	
FX320	310/60	.01/.001	200	1		300	1/5	50	2	100	200	1	
FX3200	3100/600	.1/.01	2K	1		3K	1/5	500	2	1K	2K	1	
FX40	40	.0001	20	1	1/S	40	2	20	2	20	20	2	
FX400	400	.001	400	1	1/S	400	1	200	2	200	200	3	
FX4000	4K	.01	4K	1	1/S	4K	1	2K	3	2K	2K	2	
FX6000	6K	.1	5K	1	3	5K	1	2K	1	3K	3K	1	
FY2000	2K	.1	2K	1	4/P	2K	1	1K	2	1K	1K	2	
FY300	300	.01	200	1	4/P	3K	1	200	2	100	200	1	
FY3000	3K	.1	2K	1	4/P	3K	1	2K	2	1K	2K	1	
HA120M	120	.0001	100	2	*	100	2	50	2	50	50	2	
HA180M	180	.0001	150	2	*	150	2	50	2	50	100	2	
HF200	200	.001	200	1	2	200	1	100	2	100	100	1	
HF2000	2K	.01	2K	1	2	2K	1	1K	2	1K	1K	1	
HF300	300	.001	300	1	1/S	300	1	100	2	100	100	1	
HF3000	3K	.01	3K	1	1/S	3K	1	1K	2	1K	2K	1	
HF320	310/60	.01/.001	300	1		300	1/5	100	2	100	200	1	
HF3200	3100/600	.1/.01	3K	1		3K	1/5	1K	2	1K	2K	1	
HF400	400	.001	400	1	1/S	400	1	200	2	200	200	1	
HF4000	4K	.01	4K	1	1/S	4K	1	2K	2	2K	2K	1	

11/21/01

Page 2 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	A & D												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
HF6000	6K	.1	6K	1	3	5K	1	3K	2	3K	3K	1	
HF8000	8K	.1	8K	1	3	5K	1	4K	2	4K	4K	1	
HP100	101K	1	100K	1	2	50K	1	50K	2	50K	50K	2	
HP102	101K/61K	.01/.001	100K	1		50K	1	50K	2	50K	50K	2	
HP12K	12	.1	10K	1	4/P	10K	1	6K	2	5K	5K	2	
HP20K	21	.1	20K	1	4/P	20K	1	10K	2	10K	10K	2	
HP22K	21K/2K	1/.1	20K	1		20K	1/5	10K	2	10K	10K	2	
HP30K	31	.1	30K	1	4/P	30K	1	15K	2	15K	15K	2	
HP40K	41	.5	40K	5	4/P	40K	5	20K	2	20K	20K	2	
HP60K	61	1	60K	1	4/P	50K	1	30K	2	30K	30K	2	
HX100	100	.0001	100	2	*	100		50	2	50	50	2	
HX3000	3K	.01	3K	1	1/S	3K		1500	2	1K	2K	2	
HX400	400	.001	400	1	1/S	400		200	2	200	200	2	
HX6000	6K	.1	6K	1	3	5K		3K	2	3K	3K	2	

11/21/01

Page 3 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Mettler												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
AB104	101	.0001	100	2	*	100	1	100	3	50	50	3	
AB204	210	.0001	200	2	*	200	1	100	3	100	100	4	
AB54	51	.0001	50	2	*	50	1	50	3	20	20	3	
AC100	80	.0001	80	1	*	50	2	50	8	40	40	5	
AC88	80/8	.001/.0001	80	1		50	2	50	8	40	40	5	
AE100	100	.0001	int	3	*	100	1	50	2	50	50	2	
AE160	160	.0001	int	3	*	100	1	50	2	50	100	2	
AE163	160/30	.0001/.00001	int	3		100	1/2	50	2	50	100	2	
AE200	200	.0001	int	1	*	200	1	80	3	100	100	3	
AE240	200/40	.0001/.00001	int	1		200	1/2	80	3	100	100	3	
AE50	50	.0001	int	1	*	50	1	50	2	20	30	1	
AG104	100	.0001	int	1	*	100	1	100	3	50	50	2	
AG204	200	.0001	int	3	*	200	1	100	3	50	50	2	
AG204DR	210/61	.001/.0001	int	1		200/50	1/2	100	3	100	100	2	
AG245	210/41	.0001/.00001	int	1		200/40	1/2	100	3	100	100	2	
AJ100	100	.0001	100	1	*	100	1	50	2	50	50	4	
AJ100L	100	.0001	100	1	*	100	1	50	2	50	50	4	
AJ150L	150	.0001	100	1	*	100	1	100	2	50	100	4	
AJ50	50	.0001	50	1	*	50	1	30	2	20	20	4	
AK160	160	.0001	100	1	*	100	1	50	3	50	100	5	
AM100	110	.0001	100	1	*	100	1	50	3	50	50	4	
AM50	51	.0001	50	1	*	50	1	30	2	20	20	4	
AT200	200	.0001	int	3	*	200	1	100	2	100	100	2	
AT201	200	.01m	int	4	*	200	3	100	15	100	100	12	
AT261	205/62	.0001/.00001	int	3	*	200	1	100	2	100	100	2	200.0001/62.00001

11/21/01

Page 4 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Mettler												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
AT400	400	.0001	int	3	*	200	1	200	2	100	100	2	
AT460	405/62	.001/.00001	int	3	1/S	400	1	200	2	100	100	2	
BB120	120	.01	100	1	4/P	100	1	100	2	50	50	1	
BB1200	1200	.1	1K	1	2	1K	1	1K	1	500	500	1	
BB240	240	.001	100	1	2	.001	1	200	3	100	100	1	
BB2400	2400	.01	1K	1	2	1K	1	2K	4	1K	1K	2	
BB244	240/40	.01/.001	100	1	2	100	1/1	200	3	100	100	1	
BB2440	2400/400	.1/.01	1K	1	2	1K	1	2K	4	1K	1K	2	
BB3	3100	1	1K	1	4/P	1K	1	2K	1	1K	2K	1	
BB300	310	.01	100	1	4/P	100	1	200	2	100	200	1	
BB3000	3100	.1	1K	1	4/P	1K	1	2K	1	1K	2K	1	
BB600	610	.1	500	1	4/P	500	1	500	1	300	300	1	
CJ150	150 ct	.001 ct	20	1	4/P	20g	1	30	2	10	20	4	
CJ500	500 ct	.001 ct	100	1	1/S	100g	1	50	2	50	50	4	
CM1200	1200 ct	.01 ct	100g	1	2	200g	1	100g	3	100	100	4	
CM200	200 ct	.001 ct	20g	1	2	40g	1	30g	2	20	20	4	
FEHD	24K	1	4K	1	4/P	20K	1	10K	1	10K	10K	1	
M3	3	.000000	100 mg	1	*	100 mg	1 ug	n/a		50	100	2	
PB1501	1510	.1	1K	1	4/P	1.5K	1	1K	2	500	1K	2	
PB1502	1510	.01	1K	1	2	1.5K	1	1K	3	500	1K	3	
PB153	151	.001	100	2	2	150	1	100	3	50	100	3	
PB3001	3100	.1	2K	1	4/P	3K	1	2K	1	1K	2K	2	
PB3002	3100	.01	2K	1	1/S	3K	1	1500	4	1K	2K	2	Mettler apprx \$550
PB3002D	3100/600	.1/.01	2K	1	4/P	3K	1	1500	4	1K	2K	2	
PB302	310	.01	200	1	4/P	300	1	200	2	100	200	3	

11/21/01

Page 5 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Mettler												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
PB303	310	.001	200	2	1/S	300	1	200	3	100	200	4	
PB303D	310/60	.01/.001	200	2	4/P	300	1	200	3	100	200	4	
PB5001	5100	.1	2K	1	3	5K	1	4K	2	2K	3K	2	
PB602	610	.01	500	1	3	500	1	500	2	300	300	3	
PB8000	8100	1	2K	1	4/P	5K	1	5K	2	4K	4K	2	
PB8001	8100	.1	4K	1	3	5K	1	5K	2	4K	4K	2	
PB801	800	.1	500	1	4/P	500	1	500	2	400	400	2	
PC16	16K	.1	15K	1	2	15K	1	10K	5	5K	10K	1	
PC180	180	.001	150	1	2	150	1	100	4	50	100	1	
PC2000	2K	.01	2K	1	2	2K	1	1K	3	1K	1K	1	
PC220	200/20	.01/.001	200	1	4/P	200	1	100	4	100	100	2	
PC24	24K	1	20K	1	4/P	20K	1	12K	1	10K	10K	2	
PC400	400	.01	400	1	4/P	400	1	200	1	200	200	1	
PC4000	4K	.1	4K	1	4/P	4K	1	2K	1	2K	2K	1	
PC440	400/40	.01/.001	400	1	4/P	400	1	200	8	200	200	5	
PC4400	4000/400	.1/.01	4K	1	4/P	4K	1	2K	6	2K	2K	5	
PC8000	8K	.1	8K	1	3	8K	1	4K	3	4K	4K	1	
PC8800	8000/800	1/.1	8K	1	4/P	8K	1	4K	3	4K	4K	1	
PE11	11K	.1	4K	1	2	10K	2	10K	3	5K	5K	3	
PE12	12K	1	4K	1	4/P	10K	1	10K	1	5K	5K	1	
PE16	16K	.1	4K	1	2	15K	2	10K	3	5K	10K	2	
PE160	160	.001	100	1	2	150	1	100	3	50	100	1	
PE1600	1600	.01	1K	1	2	1.5K	1	1K	3	500	1K	1	
PE200	200	.01	100	1	4/P	200	1	100	1	100	100	2	
PE22	22K	1	4K	1	4/P	20K	1	10K	1	10K	10K	1	

11/21/01

Page 6 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Mettler												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
PE24	24K	1	4K	1	4/P	20K	1	10K	1	10K	10K	1	
PE3000	3100	.1	1K	1	4/P	1K	1	2K	1	1K	2K	1	
PE360	300/60	.01/.001	100	1	4/P	300	1	200	4	100	200	2	
PE3600	3000/600	.1/.01	1K	1	4/P	3K	1	2K	4	1K	2K	2	
PE400	400	.01	400	1	4/P	400	1	200	1	200	200	2	
PE4000	4K	.1	4K	1	4/P	4K	1	2K	1	2K	2K	2	
PE6	6K	1	4K	1	4/P	5K	1	4K	1	2K	4K	1	
PE600	600	.01	500	1	3	500	1	400	2	300	300	1	
PE6000	6K	.1	4K	1	3	5K	1	4K	3	3K	3K	1	
PG2002	2K	.01	int	1	2	2K	1	1K	2	1K	1K	3	
PG203	200	.001	int	1	2	200	1	1K	3	100	100	5	
PG3001	3K	.1	int	1	4/P	3K	1	2K	1	1K	2K	1	
PG5001	5K	.1	int	1	4/P	5K	1	2K	1	2K	3K	1	
PG5002	5K	.01	int	1	*	5K	1	2K	2	2K	3K	3	
PG5002DR	5100/1000	.1/.01	int	1	3	5K	1	2K	2	2K	3K	3	
PG503	500	.001	int	1	*	500	1	200	2	200	300	3	
PG503DR	510/100	.01/.001	int	1	3	500	1	200	2	200	300	3	
PG8000	8100	1	int	1	4/P	8K	1	4K	1	4k	4k	1	
PG8001	8100	.1	int	1	3	8K	1	4k	1	4K	4K	1	
PG802	800	.01	int	1	3	800	1	500	2	400	400	2	
PJ2000	2K	.01	1K	1	2	2K	1	1K	2	1K	1K	2	
PJ300	300	.001	100	1	1/S	300	1	200	1	100	200	4	
PJ3000	3K	.01	2K	1	1/S	3K	1	2K	2	1K	2K	4	
PJ360	300/60	.01/.001	200	1	3	300	1	200	3	100	200	1	
PJ3600	3000/600	.1/.01	1K	1	3	3K	1	2K	3	1K	2K	1	

11/21/01

Page 7 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Mettler												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
PJ400	400	.01	100	1	4/P	400	1	200	1	200	200	1	
PJ4000	4K	.1	1K	1	4/P	4K	1	2K	2	2K	2K	1	
PJ6	6K	1	2K	1	4/P	6K	1	4K	1	3K	3K	1	
PJ600	600	.1	500	1	4/P	500	1	500	1	300	300	1	
PJ6000	6K	.1	2K	1	3	5K	1	4K	3	3K	3K	1	
PM100	100	.001	100	1	3	100	1	100	3	50	50	2	
PM11	11K	.1	4K	1	2	10K	1	10K	6	5K	5K	5	
PM1200	1200	.001	1K	1	*	1K	2	500	3	500	500	2	
PM15	16K	1	4K	1	4/P	15K	1	10K	6	5K	10K	4	
PM16	16K	.1	4K	1	2	15K	1	10K	6	5K	10K	5	
PM200	200	.001	100	1	2	200	1	100	3	100	100	2	
PM2000	2100	.01	1K	1	1/S	2K	1	1K	3	1K	1K	2	
PM2000C	2K	.01	1K	1	2		1	1K	3	1K	1K	4	
PM2000MC	2K	.001	1K	1	*		1	1K	3	1K	1K	4	
PM2500	2500	.01	1K	1	1/S	2K	1	1K	4	1K	1K	4	
PM30	30K	1	4K	1	4/P	30K	1	10K	6	10K	20K	8	
PM300	300	.01	100	1	4/P	300	1	200	4	100	200	4	
PM3000	3K	.1	1K	1	4/P	3K	1	2K	1	1K	2K	4	
PM34	30K/4K	1/.1	4K	1		30K	1	10K	6	10K	20K	5	
PM400	400	.001	200	1	1/S	400	1	200	3	200	200	4	
PM4000	4K	.01	2K	1	1/S	4K	1	2K	3	2K	2K	4	
PM400C	410	.01	200	1	4/P		1	200	3	200	200	4	
PM460	410/60	.01/.001	100	1	3	400	1	200	3	200	200	4	
PM4600	4100/600	.1/.01	1K	1	3	4K	1	2K	3	2K	2K	4	
PM4800	4100/800	.1/.01	1K	1	3	4K	1	2K	3	2K	2K	4	

11/21/01

Page 8 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Mettler												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
PM6	6100	1	2K	1	4/P	5K	1	4K	4	3K	3K	3	
PM600	600	.01	500	1	3	500	1	500	1	300	300	4	
PM6000	6100	.1	2K	1	3	5K	5	2K	3	3K	3K	2	
PM6100	6100	.01	4K	1	*	5K	1	4K	2	3K	3K	4	
PR1203	1200	.001	int	1	*	1K	1	500	2	500	500	3	
PR16000	16K	1	int	1	4/P	15K	1	6K	1	5K	10K	1	
PR2002	2K	.01	int	1	2	2K	1	1K	2	1K	1K	3	
PR2003DR	2100/400	.01/.001	int	1		2K	1	1K	3	1K	1K	5	
PR203	200	.001	int	1	2	200	1	200	2	100	100	3	
PR5001	5K	.1	int	1	4/P	5K	1	4K	2	2K	3K	2	
PR5002	5K	.01	int	1	*	5K	1	2K	2	2K	3K	3	
PR5002DR	5100/1000	.1/.01	int	1	3	5K	1	2K	2	2K	3K	3	
PR5003DR	5K	.001 v	int	1	1/S	5K	1	2K	3	2K	3K	2	
PR503	500	.001	int	1	*	500	1	200	2	200	300	3	
PR503D	500	.001v	int	1	1/S	500	1	200	2	200	300	3	
PR8000	8K	1	int	1	4/P	8K	1	4K	1	4K	4K	1	
PR8001	8K	.1	int	1	3	8K	1	4K	2	4K	4K	2	
PR8002	8K	.01	int	1	*	8K	1	4K	4	4K	4K	3	
PR8002DR	8100/1600	.1/.01	int	1	3	8K	1	4K	4	4K	4K	3	
PR802	800	.01	int	1	3	800	1	500	2	400	400	2	
PR803	800	.001	int	1	*	800	1	500	2	400	400	3	
SB12001	12100	.1	4K	1	2	10K	1	6K	3	5K	5K	2	
SB16000	16K	1	4K	1	4/P	15K	1	6K	1	5K	10K	1	
SB16001	16100	.1	4K	1	2	15K	1	6K	5	5K	10K	4	
SB16001DR	16.1K/3200	1/1	4K	1	4/P	15K	1	6K	5	5K	10K	1	

11/21/01

Page 9 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Mettler												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
SB24001DR	24100	1	4K	1	4/P	20K	1	10K	1	10K	10K	2	
SB32000	32100	1	4K	1	1/S	30K	1	10K	1	10K	20K	1	
SB32001DR	32.1K/6.4K	1/1	4K	1	4/P	30K	1	10K	5	10K	20K	1	
SB8000	8100	1	2K	1	4/P	8K	1	4K	1	4K	4K	1	
SB8001	8100	.1	4K	1	3	8K	1	4K	2	4K	4K	2	
SG16000	16K	1	int	1	4/P	15K	1	6K	1	5K	10K	5	
SG16001	16K	.1	int	1	2	15K	1	6K	5	5K	10K	4	
SG16001D	16K	.1	int	1	2	15K	1	6K	5	5K	10K	5	
SG32000	32K	1	int	1	4/P	30K	1	10K	1	10K	20K	1	
SG32001D	32K	.1	int	1	1/S	30K	1	10K	5	10K	20K	4	
SG8001	8K	.1	int	1	3	8K	1	3K	3	4K	4K	3	
SM1220	12K/2K	1/1	4K	1	4/P	10K	1	6K	6	5K	5K	4	
SM3000	3K	.1	1K	1	4/P	3K	1	3K	3	1K	2K	4	
SM30000	30K	1 v	4K	1	4/P	30K	1	10K	6	10K	20K	8	
SM6000	6K	.1	2K	1	3	5K	1	4K	4	3K	3K	4	
SR16001	16K	.1	int	1	2	15K	1	6K	5	5K	10K	4	
SR16001DR	16.1K/3200	1/1	int	1	4/P	15K	1	6K	5	5K	10K	5	
SR32000	32K	1	int	1	4/P	15K	1	10K	1	10K	20K	1	
SR32001	32K	.1	int	1	1/S	30K	1	10K	5	10K	20K	4	
SR32001DR	32.1K/6400	1/1	int	1	3	30K	1	10K	5	10K	20K	5	
SR8001	8K	.1	int	1	3	8K	1	3K	3	4K	4K	3	
UM3	3	.0000000	10 mg	1	*	10 mg	1 ug	n/a		5 mg	10 mg	1	
UMT2	2	.1 ug	int	2	*	2	3		0	1	1	1	

11/21/01

Page 10 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Ohaus												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
AP110	110	.0001	int	1	*	100	1	x	0	50	50	3	
AP210	210	.0001	int	1	*	200	1	x	0	100	100	3	
AP250D	210	.0001 v	int	1	*	200	1	x	0	100	100	3	
AP310	310	.0001	int	1	*	300	1	x	0	100	200	7	
B300	300	.01	300	1	4/P			150	1	100	200	1	
B3000D	3000/300	.1/.01	3K	1	4/P			1500	1	1K	2K	1	
B300D	300/30	.01/.001	300	1	4/P			150	1	100	200	1	
B5000	5K	.1	5K	1	4/P			2500	1	2K	2K	1	
E00640	62	.0001	50	1	*	50	1	30	3	30	30	3	
E01140	110	.0001	100	1	*	100	1	50	3	50	50	3	
E02130	210	.001	200	1	1/S	200	1	100	3	100	100	3	
E02140	210	.0001	200	1	*	200	1	100	3	100	100	3	
E04130	410	.001	200	1	*	400	1	200	3	200	200	3	
E06120	610	.01	500	1	3	500	1	300	3	300	300	3	
E0B120	2100	.01	2K	1	1/S	2K	1	1K	3	1K	1K	3	
E0D110	4100	.1	4K	1	4/P	4K	1	2K	3	2K	2K	3	
E0D120	4100	.01	4K	1	*	4K	1	2K	3	2K	2K	3	
E0F110	6100	.1	5K	1	3	5K	1	3K	3	3K	3K	3	
E0H110	8100	.1	8K	1	3	8K	1	4K	3	4K	4K	3	
E0K210	12K	.1	10K	1	2	10K	1	6K	3	6K	6K	3	
E0L210	22K	.1	2 K	1	1/S	20K	1	10K	3	10K	10K	3	
E0M210	32K	.1	30K	1	1/S	30K	1	15K	3	15K	15K	3	
E0RR80	210	.001 v	200	1	1/S	200	1	100	3	100	100	3	
E0RV70	410	.01 v	200	1	4/P	400	1	200	3	200	200	3	
E0RW60	4100	.1 v	4K	1	4/P	4K	1	2K	3	2K	2K	3	

11/21/01

Page 11 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Ohaus												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
E10640	62	.0001	int	1	*	50	1	30	3	30	30	3	
E11140	110	.0001	int	1	*	100	1	50	3	50	50	3	
E120	120	.001	100	1	2	100	1	50	1	50	50	1	
E12130	210	.001	int	1	1/S	200	1	100	3	100	100	3	
E12140	210	.0001	int	1	*	200	1	100	3	100	100	3	
E14130	410	.001	int	1	*	400	1	200	3	200	200	3	
E16120	610	.01	int	1	3	500	1	300	3	300	300	3	
E1B120	2100	.01	int	1	1/S	2K	1	1K	3	1K	1K	3	
E1D110	4100	.1	int	1	4/P	4K	1	2K	3	2K	2K	3	
E1D120	4100	.01	int	1	*	4K	1	2K	3	2K	2K	3	
E1F110	6100	.1	int	1	3	5K	1	3K	3	3K	3K	3	
E1H110	8100	.1	int	1	3	8K	1	4K	3	4K	4K	3	
E1K210	12K	.1	int	1	2	10K	1	6K	3	6K	6K	3	
E1L210	22K	.1	int	1	1/S	20K	1	10K	3	10K	10K	3	
E1M210	32K	.1	int	1	1/S	30K	1	15K	3	15K	15K	3	
E1RR80	210	.001 v	int	1	1/S	200	1	100	3	100	100	3	
E1RV70	410	.01 v	int	1	4/P	400	1	200	3	200	200	3	
E1RW60	4100	.1 v	int	1	4/P	4K	1	2K	3	2K	2K	3	
E300	300	.01 v	300	1	4/P	300	1	150	1	100	100	1	
E3000D	3K	.1	3K	1	4/P	3K	1	1500	1	1K	2K	1	
E300DJ	300	.01 v	300	1	4/P	300	1	150	1	100	200	1	
E400	400	.01	400	1	4/P	400	1	200	1	200	200	1	
E4000	4K	.1	4K	1	4/P	4K	1	2K	1	2K	2K	1	
G110	110	.0001	int	1	*			100	1	50	50	3	
G120	120	.001	100	1	2			50	1	50	50	1	

11/21/01

Page 12 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

Ohaus

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
G1200	1200	.01	1K	1	2			500	1	500	500	1	
G160	160	.0001	int	1	*			150	1	50	100	3	
G160D	160/30	.0001/.00001	int	1	*			150	1	50	100	3	
G200	200	.0001	int	1	*			200	1	100	100	3	
G400	400	.01	400	1	4/P			200	1	200	200	1	
G4000	4K	.1	4K	1	4/P			2K	1	2K	2K	1	
G4000D	4000/400	.1/.01	4K	1	4/P			2K	1	2K	2K	1	
G400D	400/40	.01/.001	400	1	4/P			200	1	200	200	1	
GA110	110	.0001	int	3	*			100	1	50	50	3	
GA200	200	.0001	int	3	*			200	1	100	100	3	
GA200D	200/40	.0001/.00001	int	3	*			200	1	100	100	3	
GT210	200	.001	200	1	2			100	1	100	100	1	
GT2100	2K	.01	2K	1	2			1K	1	1K	1K	1	
GT2100ad	2100	.01	2K	1	1/S	2K	1	1K	1	1K	1K	2	
GT210adv	210	.001	200	1	1/S	200	1	100	1	100	100	2	
GT310adv	310	.001	300	1	1/S	300	1	150	1	100	200	2	
GT4000ad	4K	.1	4K	1	4/P	4K	1	2K	1	2K	2K	1	
GT400adv	400	.01	400	1	4/P	400	1	200	1	200	200	1	
GT410	400	.01	400	1	4/P	400	1	200	1	200	200	1	
GT4100	4K	.1	4K	1	4/P	4K	1	2K	1	2K	2K	1	
GT4100ad	4100	.01	4K	1	*	4K	1	2K	1	2K	2K	2	
GT4100D	4100/1000	.1/.01	4K	1	4/P	4K	1	2K	1	2K	2K	2	
GT410adv	410	.001	400	1	*	400	1	200	1	200	200	2	
GT410D	410/100	.01/.001	400	1	4/P	400	1	200	1	200	200	2	
GT480	400/80	.01/.001	400	1	4/P	400	1	200	1	200	200	1	

11/21/01

Page 13 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Ohaus												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
GT4800	4000/800	.1/.01	4K	1	4/P	4K	1	2K	1	2K	2K	1	
GT8000	8K	.1	8K	1	3	8K	1	4K	1	4K	4K	1	
GT8000ad	8K	.1	8K	1	3	8K	1	4K	1	4K	4K	1	
GT8000Ta	8K	.1	8K	1	3	8K	1	4K	1	4K	4K	1	
MB200	200	.01	200	1	4/P	200	1	100	1	100	100	1	
TP200S	200	.001	200	1	2	200	1	100	3	100	100	3	
TP2KS	2K	.01	2K	1	2	2K	1	1K	3	1K	1K	3	
TP400D	400/80	.01/.001	400	1	4/P	400	1	200	3	200	200	3	
TP400S	400	.01	400	1	4/P	400	1	200	3	200	200	3	
TP4KD	4000/400	.1/.01	4K	1	4/P	4K	1	2K	3	2K	2K	3	
TP4KS	4K	.1	4K	1	4/P	4K	1	2K	3	2K	2K	3	
TP600S	600	.01	500	1	3	500	1	300	3	300	300	3	
TS120	120	.001	100	1	2	100	1	50	3	50	50	3	
TS120S	120	.001	100	1	2	100	1	50	3	50	50	3	
TS400D	400/40	.01/.001	400	1	4/P	400	1	200	3	200	200	3	
TS400S	400	.01	400	1	4/P	400	1	200	3	200	200	3	
TS4KD	4000/400	.1/.01	4K	1	4/P	4K	1	2K	3	2K	2K	3	
TS4KS	4K	.1	4K	1	4/P	4K	1	2K	3	2K	2K	3	
V00640	62	.0001	50	1	*	50	1	30	4	30	30	3	
V01140	110	.0001	100	1	*	100	1	50	4	50	50	3	
V02130	210	.001	200	1	1/S	200	1	100	3	100	100	3	
V02140	210	.0001		1	*	200	1		4	100	100	3	
V04130	410	.001	400	1	*	400	1	200	3	200	200	3	
V06120	610	.01	500	1	3	500	1	300	3	300	300	3	
V0B120	2100	.01	2K	1	1/S	2K	1	1K	3	1K	1K	3	

11/21/01

Page 14 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Ohaus												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
V0D110	4100	.1	4K	1	4/P	4K	1	2K	3	2K	2K	3	
V0D120	4100	.01	4K	1	*	4K	1	2K	3	2K	2K	3	
V0F110	6100	.1	5K	1	3	5K	1	3K	3	3K	3K	3	
V0H110	8100	.1	8K	1	3	8K	1	4K	3	4K	4K	3	
V0K210	12000	.1	12K	1	2	10K	1	6K	3	6K	6K	3	
V0L210	22K	.1	20K	1	1/S	20K	1	10K	3	10K	10K	3	
V0M210	32K	.1	30K	1	1/S	30K	1	15K	3	15K	15K	3	
V0RR80	210	.0001	200	1	*	200	1	100	4	100	100	3	
V0RV70	410	.01 v	400	1	4/P	400	1	200	3	200	200	3	
V0RW60	4100	.1 v	4K	1	4/P	4K	1	2K	3	2K	2K	3	
V10640	62	.0001	int	1	*	50	1	30	4	30	30	3	
V11140	110	.0001	int	1	*	100	1	50	4	50	50	3	
V12130	210	.001	int	1	1/S	200	1	100	3	100	100	3	
V12140	210	.0001		1	*	200	1		4	100	100	3	
V14130	410	.001	int	1	*	400	1	200	3	200	200	3	
V16120	610	.01	int	1	3	500	1	300	3	300	300	3	
V1B120	2100	.01	int	1	1/S	2K	1	1K	3	1K	1K	3	
V1D110	4100	.1	int	1	4/P	4K	1	2K	3	2K	2K	3	
V1D120	4100	.01	int	1	*	4K	1	2K	3	2K	2K	3	
V1F110	6100	.1	int	1	3	5K	1	3K	3	3K	3K	3	
V1H110	8100	.1	int	1	3	8K	1	4K	3	4K	4K	3	
V1K210	12000	.1	int	1	2	10K	1	6K	3	6K	6K	3	
V1L210	22K	.1	int	1	1/S	20K	1	10K	3	10K	10K	3	
V1M210	32K	.1	int	1	1/S	30K	1	15K	3	15K	15K	3	
V1RR80	210	.0001	int	1	*	200	1	100	4	100	100	3	

11/21/01

Page 15 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

<i>Model</i>	Ohaus												<i>Note</i>
	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
V1RV70	410	.01 v	int	1	*	400	1	200	3	200	200	3	
V1RW60	4100	.1 v	int	1	4/P	4K	1	2K	3	2K	2K	3	

11/21/01

Page 16 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

Sartorius

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
1401	2200	.1	1K	1	4/P	2K	1	1.5K	3	1K	1K	1	
1402	300	.01	200	1	4/P	300	1	300	3	100	200	1	
1403MP7	5500	.1	5K	1	3	5K	1	5K	3	2K	3K	1	
1403MP8	6K	.1	6K	1	3	5K	1	5K	3	3K	3K	1	
1404	2200	.01	2K	1	1/S	2K	1	2K	3	1K	1K	1	
1405	220	.001	200	1	1/S	200	1	200	3	100	100	1	
1406	4200	.1	4K	1	4/P	4K	1	3K	3	2K	2K	1	
1409	600	.01	500	1	3	500	1	600	3	300	300	1	
1412	300/30	.01/.001	300	1	4/P	300	1	300	3	100	200	1	
1413	5000/500	.1/.01	5K	1	3	5K	1	5K	3	2K	3K	1	
1416	3000/300	.1/.01	3K	1	4/P	3K	1	3K	3	1K	2K	1	
1419	600/60	.01/.001	600	1	3	3K	1	600	3	300	300	1	
1474	1600	.01	1500	1	2	1K	2	1.5K	3	500	1K	1	
1475	420	.001	400	2	*	400	2	400	3	200	200	1	
1501	11K	.1	10K	0	2	10K	3	10K	3	5K	5K	2	
1507	5500	.01	5K	0	*	5K	5	5K	4	2K	3K	3	
1518	2K	.001/.01	2K	2	2	2K	2	400	3	1K	1K	2	
1574	4K	.01/.1	4K	2	4/P	4K	1	4K	6	2K	2K	3	
1601	160	.0001	100	1	*	100	1	160	3	50	100	1	
1702	200	.000 1	int	1	*	200	1	200	3	100	100	2	
1712	160	.000 1v	int	1	*	30	2	30	4	50	100	2	
1773	300	.000 5v	int	1	*	300	5		5	100	200	5	
1801	111	.0001	int	2	*	100	1	100	3	50	50	2	
1872	160	.0005	int	2	1/S	100	1	150	3	50	100	5	
A120	102	.0001	100	1	*	100	1	120	3	50	50	2	

11/21/01

Page 17 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

Sartorius

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
A200S	200	.0001	150	1	*	200	2	200	3	100	100	2	
AC121S	120	.0001	int	3	*	100	1	100	3	50	50	2	
AC211P	210/120/60	.5/.2/.1mg	int	3	*	200	1	100	3	100	100	2	
AC211S	210	.0001	int	3	*	200	2	100	3	100	100	2	
BA2100	2100	.01	2000	1	4/P	2000	1	2000	4	1000	1000	2	
BA3100P	3100/1200/600	.05/.12/.01	1000	1	4/P	3000	1	3000	6	1000	2000	1	
BA4100	4100	.1	2000	1	4/P	4000	1	4000	1	2000	2000	1	
BA610	610	.01	500	1	4/P	600	1	500	4	200	300	1	
BA6100	6100	.1	5000	1	4/P	6000	1	5000	4	2000	3000	1	
BP110	110	.001	100	1	2	100	1	100	3	50	50	2	
BP110S	110	.0001	int	3	*	100	1	100	3	50	50	2	
BP1200	1200	.01	1000	1	2	1K	1	1K	3	500	500	2	
BP12000S	12K	.1	10K	2	2	10K	1	10K	3	5K	5K	5	
BP16000S	16K	.1	15K	2	2	15K	1	10K	3	5K	10K	5	
BP160S	160	.001	int	3	2	150	1	100	3	50	100	2	
BP2100	2100	.1	2000	1	4/P	2K	1	2K	3	1K	1K	2	
BP2100S	2100	.01	2000	1	1/S	2K	1	2K	3	1K	1K	2	
BP300S	300	.0001	int	3	*	300	2	100	3	100	200	3	
BP3100P	3100/1200/600	.05/.02/.01	3000	1	3	3K	1	3K	3	1K	2K	2	
BP3100S	3100	.01	3000	1	1/S	3K	1	3K	0.4	1K	2K	2	
BP310P	310/120/60	.005/.002/.001	300	5	3	300	1	300	5	100	200	5	
BP310S	310	.001	300	1	1/S	300	1	300	3	100	200	2	
BP34	34K	1	30K	2	4/P	30K	1	30K	5	10K	20K	5	
BP34000P	34/16/8K	.5/.2/.1	30K	2	3	30K	1	30K	5	10K	20K	5	
BP410	410	.01	400	1	4/P	4K	1	400	3	200	200	2	

11/21/01

Page 18 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

Sartorius

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
BP4100	4100	.1	4000	1	4/P	4K	1	4K	3	2K	2K	2	
BP61	61	.0001	int	3	*	50	1	50	3	30	30	2	
BP610	610	.01	600	1	3	500	1	500	3	300	300	2	
BP6100	6100	.1	5000	1	3	5K	1	5K	3	3K	3K	2	
E12000S	12K	.1	10K	1	2	10K	1	10K	3	5K	5K	1	
E1200S	1200	.001	1K	1	*	1K	1	1K	3	1K	1K	2	
E2000D	2K	.01 v	2K	1	2	2K	2	2K	1	1K	1K	1	
E5500S	5500	.01	5K	2	*	5K	3	5K	10	2K	3K	4	
E8100P	8100	.1 v	5K	1	4/P	8K	1	5K	1	4K	4K	1	
EK1200A	1200	.1	1K	1	4/P	1K	1	na	0	500	500	1	
F32000S	32K	.1	30K	1	1/S	30K	1	10	5	10K	20K	1	
F61	61K	1 v	50K	1	3	50K	1	20	3	30K	30K	2	
F61S	61K	1	50K	1	3	50K	1	20	2	30K	30K	2	
G1500D	1500	.1	1.5K	1	4/P			1K	2	500	500	1	
I1000	1100	.01	1	1	2	1K	1	1	2	500	500	2	
I12000S	12.1K	.1	10K	1		10K	1	10K	0.4	5K	5K	0.1	
I2000D	2000	.01 v	2	1	1/S	1K	3	2	1	1K	1K	1	
I24000P	24.2/15/6/3	1/.5/.2/.1	20K	1		20K	1	8K	1	10K	10K	0.7	
I25S	12.5K	.1	10K	0.1		10K	.1	10K	0.4	5K	5K	0.1	
I31	31K	1	15K	1	4/P	10K	1	10K	1	10K	20K	1	
I4800P	4800	.1 v	4	1	3	4K	1	4	0.06	2K	2K	1	
I50P	24.2/15/6/3	1/.5/.2/.1	20K	1		20K	1	8K	1	10K	10K	0.7	
I6800	6860	.1	5K	1	4/P	5K	1	5K	0.3	3K	3K	0.1	
I8100	8100	.01/.1	5k	0.1		8k	.1	8k	0.08	4k	4k	0.05	
I8100P	8.1/4/1.6/.8	.1/.05/.02/.01	5K	1	4/P	5K	1	8K	0.08	3K	5K	0.05	

11/21/01

Page 19 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

Sartorius

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
IB16000S	16K	.1	10K	1	2	10K	1	10K	10	5K	10K	2	
IB31	31K	1	10K	1	4/P	20K	1	10K	3	10K	20K	1	
IB31000P	31K	1 v	10K	1	4/P	20K	1	10K	2	10K	20K	1	
L2200P	2200	.05 v	2K	1	3	2K	1	2K	4	1K	1K	5	
L2200S	2200	.01	2K	1	1/S	2K	2	2K	4	1K	1K	5	
L220S	220	.001	200	1	1/S	200	1	200	3	100	100	2	
L310	310	.01	300	1	4/P	300	1	300	2	100	200	1	
L420D	420	.01 v	400	1	4	400	1	400	2	200	200	1	
L420P	420	.005 v	400	1	3	400	1	400	10	200	200	5	
L420S	420	.001	400	1	*	400	1	400	4	200	200	2	
L610	610	.01	600	1	3	500	1	600	3	300	300	1	
L610D	610	.01 v	600	1	3	500	1	600	3	300	300	1	
LC6201S				0					0			0	
LP12000P	12/6/3kg	.5/.2/.1	int	2	4/P	10K	1	10K	3	5K	5K	5	
LP12000S	12K	.1	int	2	2	10K	1	10K	3	5K	5K	5	
LP1200S	1200	.001	int	3	*	1K	1	1K	3	500	500	3	
LP16000S	16K	.1	15K	2	2	15K	2	10K	5	5K	10K	3	
LP2200	2200	.1	int	5	4/P	2K	1	2K	3	1K	1K	3	
LP2200P	2200	.05 v	int	5	4/P	2K	1	2K	5	1K	1K	5	
LP2200S	2200	.01	int	1	1/S	2K	3	2K	3	1K	1K	3	
LP220S	220	.001	int	3	1/S	200	1	200	3	100	100	3	
LP3200D	3200/1000	.01/.001	int	3	1/S	3K	1	3K	3	1K	2K	3	
LP34	34K	1	30K	2	4/P	30K	1	30K	5	10K	20K	3	
LP34000P	34/16/8kg	.5/.2/.1	30K	5	4/P	8K	2	30K	5	10K	20K	5	
LP420	420	.01	int	1	4/P	400	1	400	3	200	200	2	

11/21/01

Page 20 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

Sartorius

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
LP4200	4200	.1	int	5	4/P	4K	1	4K	3	2K	2K	3	
LP4200P	4200	.01 v	int	2	4/P	4K	3	4K	3	2K	2K	3	
LP5200P	5.2/3.8/2.4/1.2K	.1/.05/.02/.01	int	2	4/P	5K	3	5K	3	2K	3K	3	
LP6200	6200	.1	int	5	3	5K	1	5K	3	3K	3K	3	
LP6200S	6200	.01	int	2	*	5K	3	5K	5	3K	3K	3	
LP620P	620/240/120	.005/.002/.001	int	3	2	500	1	500	3	300	300	5	
LP620S	620	.001	int	3	*	500	1	500	3	300	300	3	
LP820	820	.01	int	1	3	800	1	500	2	300	300	2	
M2P	5	.000 001	int	1	*	5	1		0			1	
MC210P	210	.000 01	int	1	*	200	1		0	100	100	1	
MC410S	410	.000 1	int	1	*	400	2		0	200	200	1	
MC5	5	.000 001	int	1	*	5	1		0			1	
QS32	32K	2		0					0	10K	20K	1	
QS4000	4K	.1		0					0	2K	2K	1	
QS64	64K	5		0					0	30K	30K	1	
QS8000	8K	.2		0					0	4K	4K	1	
R160D	160	.0001 v	100	1	*	150	2	160	2	50	100	1	
R160P	160	.00005 v	100	5	*	150	2	160	2	50	100	1	
R180D	180	.0001 v	100	1	*	150	2	180	2	50	100	2	
R300	300	.0001	200	2	*	300	2	300	2	100	200	3	
S4	4	.000 000 1	int	0	*	2	2		0			2	
U3600	3600	.1	2K	0	4/P			2K	3	1K	2K	1	
U3600P	3600	.05 v	3K	1	4/P			3K	6	1K	2K	1	
U4600P	4100	.1 v	4K	1	4/P			4K	1	2K	2K	1	
U5000D	5000	.05 v	5K	1	2			5K	3	2K	2K	10	

11/21/01

Page 21 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.

Sartorius

<i>Model</i>	<i>Readability</i>		<i>Calibration</i>			<i>Repeatability</i>		<i>Corner Load</i>		<i>Linearity</i>			<i>Note</i>
	<i>Capacity</i>	<i>Res</i>	<i>Weight</i>	<i>Tol</i>	<i>Class</i>	<i>Weight</i>	<i>Tol</i>	<i>Weight</i>	<i>Tol</i>	<i>Weigh</i>	<i>Preload</i>	<i>Tol</i>	
U6100	6000	.05	5K	1	2			5K	3	3K	3K	1	

11/21/01

Page 22 of 22

IES Corporation, 2324 SE 11th Avenue, Portland, OR 97214
 PHONE: 1-800-541-0852/1-503-230-0646 FAX: 1-503-235-2535 e-mail: office@iescorp.com

Note: These are field test tolerances recommended by IES, and are subject to change. They may not be identical to manufacturer tolerances.